


# WC-SYSTEM FOR DRY-WALL CONSTRUCTION VICONNECT

## PRODUCT INFORMATION

### 1 . POSITION



<b>Model</b>	<b>922476</b>
Collection	ViConnect
PROJECTS	 PLUS
Width	635 mm
Height	1120 mm
Depth	90 mm
Weight	13,8 kg
description	<p>for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc, Easy connection to flush plate via flexible cables with bayonet joint, adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200 mm, adjustment range front to wall: min 90 mm, with cistern 80 mm with wall brackets, incl. feet and fastenings, 2 times M12 WC retaining bolts adjustable to 180mm with protection plugs and nuts, installation instructions, fastening materials, without flush plate tested in accordance with DIN EN 14055</p> <p>individual packaging materials For combination with: for wall-mounted WC self-supporting powder-coated steel frame, fully pre-assembled Please order flush plate separately. front operated, button function transmitted to drain fitting via flexible cables, connection to flush plate via bayonet joint concealed cistern with insulation against condensation with dual flush 3/6 l, adjustable to 3/4,5 l, maximal flush quantity 7.5 l, filling valve Noise Class I, flexible hose for filling valve, can be tightened by hand, angle valve connection set G1/2, protection box for access opening can be cut to size, WC connecting bend 90° DN 90 (Ø 90) / with reducing sleeve DN 90 (Ø 90) / DN 110 (Ø 110) with protection cap, complete WC connection set DN 90 (Ø 90) / 180 mm, certification marks for concealed cistern: Noise Class I for dry-wall construction, Compact, with cistern 80 mm</p>



## PROJECTS

### Specification texts

ViConnect; Toilet installation system Compact; Size: 635 x 1120 x 90 mm; for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc, Easy connection to flush plate via flexible cables with bayonet joint, adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200 mm, adjustment range front to wall: min 90 mm, with cistern 80 mm; with wall brackets, incl. feet and fastenings, 2 times M12 WC retaining bolts adjustable to 180mm with protection plugs and nuts, installation instructions, fastening materials, without flush plate; tested in accordance with DIN EN 14055; individual packaging materials; For combination with: for wall-mounted WC; self-supporting powder-coated steel frame, fully pre-assembled; Please order flush plate separately.; front operated, button function transmitted to drain fitting via flexible cables, connection to flush plate via bayonet joint; concealed cistern with insulation against condensation with dual flush 3/6 l, adjustable to 3/4,5 l, maximal flush quantity 7.5 l, filling valve Noise Class I, flexible hose for filling valve, can be tightened by hand, angle valve connection set G1/2, protection box for access opening can be cut to size, WC connecting bend 90° DN 90 (Ø 90) / with reducing sleeve DN 90 (Ø 90) / DN 110 (Ø 110) with protection cap, complete WC connection set DN 90 (Ø 90) / 180 mm, certification marks for concealed cistern: Noise Class I; for dry-wall construction, Compact, with cistern 80 mm

## COLOURS

92247600 4051202338022

TECHNICAL DRAWINGS

922476

